



# Industrial Electric Air Compressor with 380V/220V Power Source refrigeration

## **Basic Information**

• Place of Origin: China • Brand Name: Damai • Model Number: DM-YSJ

• Minimum Order

Quantity:

· Packaging Details: Customized according to customers

• Delivery Time: 30 work day L/C, T/T, D/P, D/A • Payment Terms:



# **Product Specification**

· Voltage: 380V/220V Model: Compressor • Power Source: Electric

1500W • Power: 20L • Capacity:

• Frequency:

· Color: Customization • Dimensions: 50x30x40cm

50Hz/60Hz • Highlight: 220V Industrial Electric Air Compressor,

> 380V Industrial Electric Air Compressor, refrigeration unit Industrial Electric Air

Compressor

# **Product Description:**

This powerful engine air compressor is designed to provide reliable and efficient performance, with a frequency of 50Hz/60Hz. It is capable of inflating a wide range of objects including tires, sports equipment, and inflatable toys, making it a versatile tool for any household or professional setting.



Whether you are cold room ,walk in freezer ,cooling factory,freezer room, this compressor has the power and durability to get the job done quickly and efficiently.

## Features:

Product Features for Damai Compressor: Product Name: Damai Compressor

Model: Compressor Voltage: 380V/220V Type: Portable Capacity: 20L

Keywords: Air Compressor, Engine Air Compressor

### **Technical Parameters:**

| Com<br>pres<br>sor<br>type | Nomin<br>al<br>motor<br>power<br>HP/K<br>W | Dispiacemen<br>t(50Hz)m³/h |                      | Num<br>ber of<br>Cylin                      | Aspirator,<br>exhaust<br>valve<br>take-over |                   | Oil<br>inje         | Pow                            | Electrical parameter |  | Cra<br>nkca                     | Oil                                | Wei<br>ght<br>(incl                     |
|----------------------------|--|----------------------------|----------------------|---|---|-------------------|---------------------|--------------------------------|----------------------|--|---------------------------------|------------------------------------|---|
|                            |  | Low<br>Pres<br>sure        | High<br>Press<br>ure | der<br>xDia<br>meter<br>xStro<br>ke(m<br>m) | DL  | SL                | volu ply<br>me( V/9 | er<br>sup<br>ply<br>V/Ø/<br>Hz | Max oper atin        | Startin<br>g<br>current<br>/Motor<br>locked<br>current<br>(A | se<br>Heat<br>er<br>(220<br>) W | sup<br>ply<br>met<br>hod           | udin<br>g<br>free<br>zing<br>oil)K<br>g |
| 4H-<br>15.2                | 15/10.<br>5                                |                            | 73.6                 | 4хФ7<br>0х55                                | Ø28<br>1-<br>1/8                            | Ø42<br>1-<br>5/8" | 4.5                 | 380                            | 31                   | 81/132   | 140                             |                                    | 197                                     |
| 4H-<br>25.2                | 25/18.<br>5                                |                            | 73.6                 | 4хФ7<br>0х55                                | Ø28<br>1-<br>1/8"                           | Ø54<br>2-<br>1/8" | 4.5                 | 420<br>YY/<br>3/50             | 45                   | 116/19<br>3  | 140                             | Forc<br>ed-<br>lubri<br>cati<br>on | 205                                     |
| 4G-<br>20.2                | 20/15                                      |                            | 84.5                 | 4хФ7<br>5х55                                | Ø28<br>1-<br>1/8                            | Ø54<br>2-<br>1/8" | 4.5                 | 440<br>~48<br>0YY              | 37                   | 97/158   | 140                             |                                    | 200                                     |
| 4G-<br>30.2                | 30/22                                      |                            | 84.5                 | 4хФ7<br>5х55                                | Ø28<br>1-<br>1/8                            | Ø54<br>2-<br>1/8" | 4.5                 | /3/6<br>0                      | 53                   | 135/22   | 140                             |                                    | 209                                     |

### **Applications:**

With a voltage range of 380V or 220V, it is suitable for use in both industrial and commercial settings. Its dimensions of 50x30x40cm make it compact and easy to install in tight spaces. Additionally, the DM-YSJ compressor is customizable in color, allowing it to blend effortlessly with its surroundings.



This compressor is also a great choice for walk-in freezer air compressors. Its durable construction ensures that it can withstand the harsh conditions of low temperatures and high humidity. It is also easy to maintain and has a long service life, making it a reliable option for any business that requires a walk-in freezer air compressor.

In summary, the Damai DM-YSJ compressor is a versatile and reliable machine suitable for a wide range of applications. Its customizable color, compact design, and high power make it a valuable addition to any workspace. Whether you need a piston compressor for your industrial setting, air compressor head for your pneumatic tools, or a walk-in freezer air compressor, the DM-YSJ compressor is the perfect solution.

## **Support and Services:**

The Damai Compressor product comes with a comprehensive technical support and services package to ensure the highest level of customer satisfaction. Our team of experienced technicians is available to answer any product-related questions and provide guidance on proper installation, operation, and maintenance. In addition, we offer repair and replacement services for any defective components or parts. Our aim is to minimize downtime and ensure the smooth operation of your equipment. We also provide training programs for operators to maximize efficiency and productivity. Contact us for more information on our technical support and services for the Damai Compressor product.



#### **Packing and Shipping:**

Product Packaging:

The Damai Compressor will be packaged in a wodden box to ensure safe delivery. The box will be labeled with the product name and features, as well as any necessary handling instructions.

Shipping:

The Damai Compressor will be shipped by shipping to the address provided by the customer at the time of purchase. Shipping times may vary depending on location and other factors, but typically take between 3-7 business days within the continental United States.





sales3@dmllcn.com

e

coldroomunit.com

Factory No. 1, Wanfeng Aviation Town, Wozhou Town, Xinchang County, Zhejiang Province