



Refcomp SRC-S(W)-885 SRC-S-885-L4 High Temperature Refrigeration Screw AC Compressor

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Refcomp
- Certification: CE
- Model Number: SRC-S(W)-885, SRC-S-885-L4
- Minimum Order Quantity: 1
- Price: Discussed
- Packaging Details: WOODEN CASE
- Delivery Time: 1 Month
- Payment Terms: Western Union, T/T
- Supply Ability: 100000Pcs/Year



Product Specification

- Refrigerant: R22, R407C, R410a, R404A, R507A
- Oil Charge: 25L
- Rated Power: 270HP/201KW
- Displacement 50/60Hz: 1000/1200 M3/hr
- Application: HVAC, Condensing Unit, Cold Room, Rack System
- Highlight: **Refcomp SRC-S-885 screw compressor, high temperature refrigeration screw compressor, SRC-S-885-L4 AC screw compressor**



More Images



for more products please visit us on coldroomunit.com

Product Description

Product Description

- High-Efficiency Asymmetric Rotor Profile:** Optimized rotor geometry ensures smooth meshing engagement and continuous gas displacement, maximizing efficiency for heavy-duty commercial HVAC systems.
- Heavy-Duty Bearing & Structural Design:** Precision axial bearings and high-load mechanical design support low-vibration continuous operation with a design life of up to 100,000 hours.
- Integrated Multi-Stage Oil Separation:** Built-in internal oil separator achieves up to 99.85% separation efficiency, significantly reducing oil carryover to keep system heat exchangers clean.
- Comprehensive Motor Thermal Protection:** Equipped with an INT69 SNY protection module and 6 internal PTC thermistors for continuous real-time monitoring of motor winding and discharge gas temperatures.

Product Image



Technical Specification

Model	SRC-S(W)-885	SRC-S-885-L4
Rated power	270HP / 201KW	
Exhaust volume (50Hz / 60Hz)	1000 / 1200 m³/hr	
Refrigerant Type	R22, R407C, R410a, R404A, R507A	
Weight	1400 KG	
Oil Charge	25 L	
Voltage	400/3/50Hz – 460/3/60Hz	
Cooling Capacity Regulation	100%, 75%, 50%, 25% (stepless 100%–25%)	
LRA Y/Δ	876 / 2627A	1062 / 3186A

Model SRC-S(W)			353	413	463	503	553	603	755	785	885	985	
Standard Motor Power		HP/kW	120/90	140/105	160/120	180/135	200/150	220/164	220/164	240/179	270/201	300/224	
Displacement 50/60[Hz]		m³/h	402/482	445/534	510/612	562/674	600/720	700/840	860/1030	910/1092	1000/1200	1100/1320	
Weight		kg	730	740	775	1010	1030	1020	980	1400	1400	1400	
Oil Charge		dm³	14		16	19		20	23	25			
Electrical Heater			275W-230V-50/60Hz										
Discharge pipe inner diameter/pipe size		mm	80.0/3-1/8"							105.5/4-1/8"			
Suction pipe inner diameter/pipe size		mm	92.5/3-5/8"			105.5/4-1/8"				134.8/0133			
Liquid Injection Connection		mm	10(copper pipe)										
Economizer Connection		mm	28			42		28	42				
Cooling Capacity Regulation			100%,75%,50%,25%(stepless 100%-25%)										
Protection Device			INT69 SNY										
Lubricating Oil			R22:S001,R407C、 R404A、 R507:S002										
Compressor Positioning Hole			4×Ø19										
Standard Motor			400/3/50Hz-460/3/60Hz										
Y/Δ	SRC-S-W	LRA Y	A	276	354	374	453	543	543	595	783	876	1062
		LRA Δ	A	876	1155	1155	1333	1645	1645	1802	2348	2627	3186
		FLA	A	195	210	230	265	290	320	418	475	540	590
	SRC-S	LRA Y	A	354	374	453	543	595	595	595	876	1062	1062
		LRA Δ	A	1155	1155	1333	1645	1802	1802	1802	2627	3186	3186
		FLA L	A	225	245	270	300	334	400	418	520	590	650

Frequently Asked Questions

Q: What technical parameters are required when evaluating the SRC-S(W)-885 (SRC-S-885-L4) screw AC compressor for system integration?

A: You should provide target cooling capacity, design evaporating and condensing temperatures, refrigerant type, power supply specifications, and whether economizer subcooling or liquid injection is required.

Q: What essential checks should be performed on the oil circuit and suction filter prior to commissioning?

A: Pre-heat the crankcase via the 275W electrical heater before startup to prevent liquid migration, verify that the oil level is visible in the sight glass, and inspect suction strainer cleanliness.

Q: How does the built-in INT69 SNY protection system operate in real-time?

A: The INT69 SNY module processes temperature signals from six embedded PTC thermistors inside the motor windings and discharge chamber, automatically tripping the control circuit if over-temperature limits are reached.

Q: What routine servicing tasks maintain compressor stability and lubricant performance over long duty cycles?

A: Regularly inspect oil sight glass clarity, monitor pressure drops across suction strainers and oil filters, and check terminal box wiring tightness during routine service inspections.